

# NOVA 15-25-B12 P30 LW


Inrunner BLDC motor with closed housing

## Overview

The NOVA 15 Light-Weight ("LW") is from our family of super rugged inrunner BLDC motors and has been specifically designed for the most demanding applications, including uncrewed systems and aerospace.

## Features

- Super robust housing for mission critical applications in the harshest environments
- Best power-to-weight-to-robustness ratio in its class
- Position and temperature sensors included in standard
- Optimized shaft for Plettenberg propeller coupling




## Specifications

Peak output power	7	kW
Peak torque <sup>1</sup>	20	Nm
Max. speed	8,000	rpm
Voltage range	40-120	V
Speed constant (kV)	64	rpm/V
Diameter	138	mm
Length	65	mm
Weight	1,800	g
Phase cable length	100	mm
Sensor cable length	400	mm
Protection class	IP54	
Mounting	Front & back	
Cooling	Air cooled	
Ambient Temperature range	-20 to +60	°C
Max. temperature of stator (as measured by sensor)	+100	°C
Position sensor types	Hall effect sensor with UVW-commutation signals	
Temperature sensor	NTC 47 kΩ	
Number of poles	30	
Number of windings	12	
Peak thrust	40 kg with 36x12" prop	

## Complementary Products


- Plettenberg propeller coupling: PC LW 6K 12mm
- Plettenberg ESCs: MST 60-260, MST 60-290, MST 60-130, MST 80-240, MST 80-350, MST 140-200
- Plettenberg gold connectors: GC6-00 / GC6-90

## Heatmap



Notes:

<sup>1</sup> With sensor-guided ESC



Plettenberg Elektromotoren GmbH & Co. KG  
 Rostocker Straße 30  
 34225 Baunatal, Germany  
 T: +49 (0) 56 01 97 96-0  
 www.plettenbergmotors.com / sales@plettenbergmotors.com  
 © 2024 Plettenberg Elektromotoren GmbH & Co. KG. All rights reserved.

